



Two Pass
on Water
Side

Oil Cooler Model No.	A Over All Length	B Port to Port	C	D Dia. Water Port	E Dia. Shell	F	G Bracket Spacing	H Bracket Slot Size	J Oil Port Connection Type	K C.L. to Port	L C.L. to Brkt.
3-1105A	15.33	8.12	3.6	3	5.3	3.54	8.25	.38 x .50	1-11.5 NPTF	3.3	3.75
3-1127A	15.5	8.12	3.69	3	6.32	2.94	9.62	.44 x .75	1.25-11.5 NPTF	4.75	4.12
3-1178A*	15.63	9.6	3.01	2.25	4.5	4.31	7	.38 x .62	.75-14 NPT	2.88	2.88
3-1179B	25.62	16.95	4.34	3	6.32	3.94	17.75	.44 x .75	2-11.5 NPTF	4.75	4.12
3-1192A	14.44	8.12	4.12	2.25	6.32	3.25	9.62	.44 x .75	1.25-11.5 NPTF	4.75	4.12
3-1234A	15.33	8.12	3.6	3	5.3	3.54	8.25	.38 x .50	1-11.5 NPTF	3.3	3.75
3-1249T	19.38	12	3.69	3	5	3.94	11.5	.38 x .50	1.312-12 UN-2B O-RING BOSS	3.75	3.75
3-1255A	14.95	8.12	2.02	2.25	5.3	2.5 1 at 8°	8.25	.38 x .50	.75-14 NPT	3.25	3.75
3-1259B	19.75	12	3.88	3	6.32	3.88	12	.44 x .75	1.625-12 UN-2B O-RING BOSS	4.16	4.12

3-1270A	18.54	12	4.25	2.75	6.32	3.38	12	.44 x .75	1.625-12 UN-2B O-RING BOSS	4.16	4.12
3-1274B	24.55	16.95	4.77	2.75	6.32	3.38	17.75	.44 x .75	1.625-12 UN-2B O-RING BOSS	4.16	4.12
3-1277D	19.75	12.5	3.63	3	4.5	4.13	11.5	.38 x .50	1.312-12 UN-2B O-RING BOSS	3.5	3.5
3-1279B	25.62	16.95	4.34	3	6.32	3.94	17.75	.44 x .75	1.625-12 UN-2B O-RING BOSS	4.16	4.12
3-1279C	25.62	16.95	4.34	3	6.32	3.94	17.75	.44 x .75	1.625-12 UN-2B O-RING BOSS	4.16	4.12